



M/s. Chhaganlal Dharamchand Shah

ASTM SEAMLESS RED BRASS AND COPPER PIPE

SIZE (IPS)	OUTSIDE DIAMETER	REGULAR				EXTRA STRONG			
		INSIDE DIAMETER	WALL THICKNESS	Kg. per Foot		INSIDE DIAMETER	WALL THICKNESS	Kg. per Foot	
				Brass	Copper			Brass	Copper
1/8	10.3	7.1	1.58	0.114	0.117	5.2	2.54	0.165	0.168
1/4	13.7	9.6	2.08	0.202	0.207	7.5	3.12	0.277	0.283
3/8	17.1	12.6	2.29	0.284	0.29	10.7	3.23	0.376	0.384
1/2	21.3	15.9	2.72	0.423	0.433	13.7	3.79	0.558	0.566
3/4	26.7	20.9	2.89	0.575	0.589	18.7	3.99	0.757	0.776
1	33.4	27.0	3.2	0.807	0.825	24.2	4.63	0.98	1.138
1 1/4	42.2	34.7	3.7	1.19	1.219	32.3	4.93	1.537	1.569
1 1/2	48.3	40.6	3.81	1.419	1.451	37.9	5.15	1.86	1.906
2	60.3	52.4	3.96	1.868	1.913	49.1	5.62	2.571	2.636
2 1/2	73.0	63.5	4.75	2.716	2.775	58.8	7.11	3.927	4.013
3	88.9	77.8	5.56	3.882	3.972	73.4	7.72	5.26	5.351
3 1/2	101.6	88.9	6.35	5.079	5.17	85.3	8.15	5.488	6.53
4	114.3	101.6	6.35	5.759	5.85	96.9	8.66	7.665	7.845
5	141.3	128.6	6.35	7.165	7.346	122.2	9.53	10.521	10.748
6	168.3	155.6	6.35	8.616	8.798	146.1	11.1	14.603	14.92
8	219.1	203.2	7.92	14.013	14.331	193.7	12.7	21.95	22.448
10	273.1	254.5	9.27	20.498	20.952	247.7	12.7	27.709	28.3
12	323.9	304.8	9.5	25.07	29.7	-	-	-	-